# LIGHTNING SPEED

# SUCCESS AT LIGHTNING SPEED

The **Lightning Cut** from **Salem Fabrication Supplies** is a premium line of high-speed, selfdressing diamond core drills. This line is part of our **Storm Series** of products and provides very smooth finish quality –even at higher feed-rates than those offered by industry standard products. Our **Lightning Cut** core drills are available in both 75 mm and 95 mm overall lengths.

# Lightning Cut – Premium Self-Dressing Diamond Core Drills – 75 mm OAL

**Salem's** premium **75 mm OAL Lightning Cut** core drills are designed for rigorous use on **CNC machines**. Ask about our premium 95 mm OAL Lightning Cut core drills for Forvet<sup>®</sup> machines!

SALEM

### **BENEFITS**

 Self-sharpening -no dressing is required

ALEM

019.05

- High feed rates with very smooth finish quality
- Stainless steel body for extra durability
- Operator friendly –easy to use
- Readily available short lead times on custom sizes
- Reduced production costs with:
  - Longer life and faster drilling speed
  - Consistent performance throughout drill life

### **USAGE INSTRUCTIONS**

- No initial dressing is needed –ready to perform right out of the box
- Capable of feeds of up to 1.8 mm/sec
  - Run at 1.4 mm/sec for cleaner cutting

#### Lightning Cut – Standard Parameters (75 mm OAL)

Ø	RPM	Feed Rate	Item #
6.35 mm	4,300	1.0 - 1.8 mm/s	DD6.35LCP
9.5 mm	2,900	1.0 - 1.8 mm/s	DD9.5LCP
10 mm	2,700	1.0 - 1.8 mm/s	DD10LCP
11 mm	2,500	1.0 - 1.8 mm/s	DD11LCP
12.7 mm	2,200	1.0 - 1.8 mm/s	DD12.7LCP
14.28 mm	2,000	1.0 - 1.8 mm/s	DD14.28LCP
15.9 mm	1,750	1.0 - 1.8 mm/s	DD15.9LCP
19.05 mm	1,450	1.0 - 1.8 mm/s	DD19.05LCP
22.3 mm	1,250	1.0 - 1.8 mm/s	DD22.3LCP
25.4 mm	1,150	1.0 - 1.8 mm/s	DD25.4LCP

The standard working parameters listed on this chart is only for **Lightning Cut** core drills and may need adjustment depending on the working conditions.

Higher feeds are possible, but may require an incremental increase of RPM.

# **CONTACT SALEM TODAY!** LEARN MORE ABOUT OUR THUNDER CUT LINE!





800.234.1982 | info@salemftg.com | www.SalemFTG.com

Salem Fabrication Supplies is a division of Salem Fabrication Technologies Group, Inc. | We Are 100% Employee Owned

# **Glass Fabrication Tooling & Supplies**



## **Diamond Tooling**

Core Drills | Countersinks | Cup Wheels | Peripheral Wheels | Routers



### Abrasives Loose Abrasives | Sanding Belts Sanding Discs | Wheel Dressing



Material Handling

Carts, Racks & Tables | Cranes Dollies | Vacuum Hand Cups Vacuum Lifters, Rotators & Tilters



Other Equipment Dual-Belt Seamers | Markers

**Polishing Products** 



# **Glazing Supplies & More**

Adhesives | Cleaners | Cork & Felt Tabs Corner Protectors | EVA Laminating Film Gloves | Hand Cutters | Protective Coatings Razor Blades | Sealants | Tape | And More



# Window Glass Products

Approved Cutting Fluids | Dual-Belt Seamers Edge Deletion Wheels | Material Handling Sanding Belts and Discs



## **Coolants & Additives**

Biocide | Coolants | Cutting Fluids Defoamer | Flocculant





Explore our full line of machinery & equipment at: HHHGlassEquipment.com

HHH Equipment Resources is a division of Salem Fabrication Technologies Group, Inc.

# CONTACT SALEM TODAY! LEARN MORE ABOUT OUR FULL LINE OF TOOLING & SUPPLIES!

Cerium Impregnated Wheels | Cerium Oxide | Cup Polishing Wheels

Edge Deletion Wheels | Felt Wheels | Peripheral Polishing Wheels





800.234.1982 | info@salemftg.com | www.SalemFTG.com

Salem Fabrication Supplies is a division of Salem Fabrication Technologies Group, Inc. | We Are 100% Employee Owned