



STM-700

STM-700 is a great low-cost coolant option for applications that have a high level of fluid loss. It is formulated to run at 5% and offers simple biological protection and rust inhibition. It can be run in most particle removal systems.

STM-700 is suitable for use with flocculants and settling agents. Specific product recommendations will be based on the particle removal system and other customer requirements.

TYPICAL SPECIFICATIONS:

Appearance	–	water / clear-slight haze
Specific Gravity	–	1.000 G/CC
Reserve Alkalinity	–	NA
PH @ 5%	–	9.0-10.0 (9.46)

BENEFITS OF USING STM-700:

- No Lubricity
- Low concentration requirement
- Very low foaming
- Biological protection
- Excellent rust protection

GO BEYOND THE EDGE

NORTH CAROLINA – HQ

5901 Gun Club Road
Winston-Salem, NC 27103
Office: 800.234.1982 | 336.766.1104

CALIFORNIA

10125 Shoemaker Avenue
Santa Fe Springs, CA 90670
Office: 800.445.6339 | 562.944.6155

PENNSYLVANIA

2330 Greensburg Road
New Kensington, PA 15068
Office: 724.212.3749

WASHINGTON

3801 NE 109th Ave. Suite C
Vancouver, WA 98682
Office: 360.993.5644

ONTARIO – CANADA

Greater Toronto Area
Office: 844.858.7444
www.SalemFTG.com