

## Cork Separator Pads with Cling Foam

### Technical Data Sheet

Items	Specification
1.Components	Plain cork; Cling foam; Plastic/Paper protective liner
2.Cork Density(kg/m <sup>3</sup> )	190±20
3.Cork Hardness	70±5
4.Tolerance of Thickness	0.2mm
5.Tolerance of Length	0.6-0.8mm
6.Adsorbability(Newton)	3±1 N/sq.cm(+20°C)
7.Acidity And Alkaescence	Neutral
8.Heat-resistant	100 Centigrade degree, over 2 hours, no residue on glass
9.Humidity-resistant	Relative humidity 95%, over 2 weeks, no residue on glass
10.Wear	Pressure 45kgs, normal temperature, 180 days, no residue on glass
11.Recommend temperature of processing	+18°C up to +40°C
12.Storage	At 18°C and about 60% relative humidity of air, clean and dry in original cardboard, to protect against UV-radiation and too high humidity of air

**GO BEYOND THE EDGE**

**NORTH CAROLINA – HQ**

5901 Gun Club Road  
Winston-Salem, NC 27103  
Office: 800.234.1982 | 336.766.1104

**CALIFORNIA**

10125 Shoemaker Avenue  
Santa Fe Springs, CA 90670  
Office: 800.445.6339 | 562.944.6155

**PENNSYLVANIA**

2330 Greensburg Road  
New Kensington, PA 15068  
Office: 724.212.3749

**WASHINGTON**

3801 NE 109th Ave, Suite C  
Vancouver, WA 98682  
Office: 360.993.5644

**ONTARIO – CANADA**

Greater Toronto Area  
Office: 844.858.7444  
[www.SalemFTG.com](http://www.SalemFTG.com)