

Rubber Separator Pads with Cling Foam Technical Data Sheet

Items	Specification
1.Components	EVA Rubber; Cling foam; Plastic/Paper protective liner
2.Rubber Density(kg/m ³)	170±20
3.Rubber Hardness	65±5
4.Tolerance of Thickness	0.2mm
5.Tolerance of Length	0.6-0.8mm
6.Adsorbability(Newton)	3±1 N/sq.cm(+20°C)
7.Acidity And Alkaescence	neutral
8.Heat-resistant	100 Centigrade degree, over 2 hours, no residue on glass
9.Humidity-resistant	relative humidity 95%, over 2 weeks, no residue on glass
10.Wear	pressure 45kgs, normal temperature, 180 days, no residue on glass
11.Recommend temperature of processing	+18°C up to +40°C
12.Storage	at 18°C and about 60% relative humidity of air, clean and dry in original cardboard, to protect against UV-radiation and too high humidity of air

GO BEYOND THE EDGE

NORTH CAROLINA – HQ

5901 Gun Club Road
Winston-Salem, NC 27103
Office: 800.234.1982 | 336.766.1104

CALIFORNIA

10125 Shoemaker Avenue
Santa Fe Springs, CA 90670
Office: 800.445.6339 | 562.944.6155

PENNSYLVANIA

2330 Greensburg Road
New Kensington, PA 15068
Office: 724.212.3749

WASHINGTON

3801 NE 109th Ave, Suite C
Vancouver, WA 98682
Office: 360.993.5644

ONTARIO – CANADA

Greater Toronto Area
Office: 844.858.7444
www.SalemFTG.com